

Quick Start Guide

Installation:

Use the ONE relay in existing installations by simply replacing the conventional SPST relay (up to 30 amps), the ONE will turn on and off with the switch the same as the conventional relay. Please note, you may notice a short delay when the switch is thrown, this is normal.

For new installations please refer to the wiring diagram included here.

Operation:

The ONE is only controllable by Bluetooth when it is in the "ON" position from the connected external switch. Once installed, the switch should be in the "ON" position before pairing or utilizing the TRIGGER App. The ONE will not connect when external switch is in the "OFF" position.

Please refer to the App for instructions on pairing and adding additional ONE

relays, up to 6 can be used in the App at once.

The App can be found on the Apple or Google play stores by searching "Trigger ACS Plus".


The blue LED indicator light shows solid when connected and flashing when searching for a connection.

Use the "RESET" button to reset the bluetooth pairing to the factory settings.

IMPORTANT: The ONE will replace most current relays without issue, but due to the variations in relay wiring, it is possible that the ONE may not operate properly. Please be sure the wiring used matches the diagram on the reverse of this sheet or on the Trigger Controller website.

PLEASE USE RESPONSIBLY, DO NOT OPERATE PHONE OR APP WHILE DRIVING! THE ONE IS INTENDED FOR OFF HIGHWAY USE AND WHEN VEHICLE IS STATIONARY. AAC ASSUMES NO LIABILITY FOR IMPROPER USE. USE AT OWN RISK.

Please go to www.triggercontroller.com for more detailed info



Please note: to operate properly, the ONE needs to switch the positive circuit, not the negative.

WARNING
Do not use phone to
operate while
driving!

AAC warranty's the ONE for 90 days from date of purchase against manufacturers defects only. AAC will not warranty items that are improperly installed or abused. Please contact us for details on our warranty policy or to arrange an RMA. No items will be accepted back without an RMA issued by AAC.

Tech Support Line: 951-339-1469

