



AMB363

Multifunctional Vehicle Tracker



Remote engine shutdown

Shutdown engine remotely from the app or web portal



Multiple alerts

Receive real-time driver behavior, geofencing, vibration and collision alerts



Trip history and trip playback

View each trip in detail in a map or satellite view. Classify trips as business or personal



SOS button

Discreet SOS button for distress alarm to the next of kin or security provider



Listen-in mode

Voice-monitor function available from two pre-registered numbers



Live Tracking

Real-time tracking via App or web portal



Multiple analog & digital I/O

Monitor and control external application via input/outputs



Built-in back up battery

Built in battery back up in case of disconnection from the vehicle battery

Application



Fleet management



Vehicle tracking



Taxi

GSM Specification

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	32+32Mb
Phase error	RMSPE<5, PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm

GPS Specification

GPS chipset	MTK high sensitivity chip
Frequency	L1, 1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTFF (open sky)	Avg. hot start ≤ 1 sec Avg. cold start ≤ 32 sec

Function & Package

Voice monitor range	≤5 meters
Battery	450mAh/3.7V Li-Polymer battery
Working voltage/current	9-36VDC
Standby time	60 hours
Working time	4 hours
Operating temperature	-20 ~ 70
Device weight	80g
Device dimension	98(L)*52 (W) *15 (H) mm

Contact

Amber Connect Limited

Add: Unit 1-3, 6 Haining Road Kingston 5, Jamaica

Tel: +1 (876) 620-5255, +1 (876) 632-6737, +1 (305) 420-6361

Web: www.amberconnect.com

Email: info@amberconnect.com